








































HIKVISION










IP ÜRÜNLER












ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
2MP IP KAMERA		
DS-2CD1023G0-IUF (Dahili mikrofon)		2MP Mini IR Bullet Kamera (H.265+) 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included
DS-2CD1323G0-IUF (Dahili mikrofon)		2MP Mini IR Dome Kamera (H.265+) 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included
DS-2CD1123G0-IUF		2MP Mini IR Dome Kamera (H.265+) 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included
DS-2CD2121G0-I		2MP Mini IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive CMOS, ICR, Color: 0.028 Lux @(F2.0; AGC ON), 0lux with IR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, DWDR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), HIK-Connect cloud service. 3-Axis Adjustment.
YENİ DS-2CD1023G2-LIUF (Dahili mikrofon)	 	2MP Mini Bullet Kamera (H.265+) Smart Hybrid Light & MD 2.0 High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);
YENİ DS-2CD1323G2-LIUF (Dahili mikrofon)	 	2MP Mini Dome Kamera (H.265+) Smart Hybrid Light & MD 2.0 High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);
YENİ DS-2CD1027G2H-LIUF (Dahili mikrofon)	  	2MP Mini Bullet Kamera (H.265+) ColorVu & Smart Hybrid Light & MD 2.0 High quality imaging with 2 MP resolution; Support Human and Vehicle Detection MD2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Built-in microphone for real-time audio security; Water and dust resistant (IP67);

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-2CD1327G2H-LIUF (Dahili mikrofon)	  	2MP Mini Dome Kamera (H.265+) ColorVu & Smart Hybrid Light & MD 2.0 High quality imaging with 2 MP resolution; Support Human and Vehicle Detection MD2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Built-in microphone for real-time audio security; Water and dust resistant (IP67);
DS-2CD2027G2-L (Powered by Darkfighter)	 	2MP Mini IR Bullet Kamera (H.265+) ColorVu High quality imaging with 2 MP resolution ; Efficient H.265+ compression technology; Clear imaging against strong back light due to 120 dB WDR technology; 24/7 colorful imaging; Focus on human and vehicle classification based on deep learning; Water and dust resistant (IP67);
DS-2CD2T26G2-4I (Powered by Darkfighter)	 	2MP IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.007 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2I/4I model: up to 50m(2Leds)/80m(4Leds) IR distance
DS-2CD1623G0-IZS		2MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, DWDR, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included -Z: motorized vari-focal lens - IP67
DS-2CD1723G0-IZS		2MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, DWDR, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included -Z: motorized vari-focal lens - IP67-IK10
YENİ DS-2CD2623G2-IZS	 	2MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 60m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
YENİ DS-2CD2723G2-IZS	 	2MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2CD2626G2-IZS (Powered by Darkfighter)	 	2MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.007 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service; Audio/Alarm I/O
DS-2CD2726G2-IZS (Powered by Darkfighter)	 	2MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.007 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service; Audio/Alarm I/O
4MP IP KAMERA		
DS-2CD1043G0-IUF (Dahili mikrofon)		4MP Mini IR Bullet Kamera (H.265+) 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included TF card slot,
DS-2CD1343G0-IUF (Dahili mikrofon)		4MP Mini IR Dome Kamera (H.265+) 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included TF card slot,
DS-2CD1143G0-IUF (Dahili mikrofon)		4MP Mini IR Dome Kamera (H.265+) 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included TF card slot,
DS-2CD2043G2-I		4MP Mini IR Bullet Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service
DS-2CD2143G2-IU		4MP Mini IR Dome Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service Built-in microphone







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-2CD1043G2-LIUF (Dahili mikrofon)		4MP Mini Bullet Kamera (H.265+) Smart Hybrid Light & MD 2.0 High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);
YENİ DS-2CD1343G2-LIUF (Dahili mikrofon)		4MP Mini Dome Kamera (H.265+) Smart Hybrid Light & MD 2.0 High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);
YENİ DS-2CD1047G2H-LIUF (Dahili mikrofon)		4MP Mini Bullet Kamera (H.265+) ColorVu ColorVu & Smart Hybrid Light & MD 2.0 High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Built-in microphone for real-time audio security; Water and dust resistant (IP67);
YENİ DS-2CD1347G2H-LIUF (Dahili mikrofon)		4MP Mini Dome Kamera (H.265+) ColorVu ColorVu & Smart Hybrid Light & MD 2.0 High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Built-in microphone for real-time audio security; Water and dust resistant (IP67);
DS-2CD2047G2-L		4MP Mini IR Bullet Kamera(H.265+)ColorVu 130dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on; 25fps/30fps(2688×1520, 2304×1296, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in microphone
DS-2CD2347G2-L		4MP Mini IR Dome Kamera(H.265+)ColorVu 130dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0014 lux (F1.0, AGC ON), 0 lux with LED on; 25fps/24fps(2592×1520,2304×1296,1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
YENİ DS-2CD2T43G2-2I		4MP Bullet Kamera (H.265+) Acusense 120dB WDR High quality imaging with 4 MP resolution; Clear imaging against strong backlight due to 120 dB WDR technology; Efficient H.265+ compression technology; Water and dust resistant (IP67) ; Focus on human and vehicle targets classification based on deep learning;







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2CD2T45G0P-I		4MP Bullet Kamera (H.265+) Super Wide Angle 120dB WDR 180°super wide field of view High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Distortion correction Water and dust resistant (IP67)
DS-2CD2T47G2-L	 	4MP Bullet Kamera (H.265+) ColorVu 130dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.00014 lux (F1.0, AGC ON), 0 lux with LED on; 25fps/30fps(2688×1520,2560×1440,1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
DS-2CD1643G0-IZS/UK		4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included -Z: motorized vari-focal lens
DS-2CD1743G0-IZS/UK		4MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included -Z: motorized vari-focal lens
DS-2CD1643G2-LIZSU (Dahili mikrofon)	 	4MP Smart Hybrit Light Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR High quality imaging with 4 MP resolution Support Human and Vehicle Detection Smart Hybrid Light: advanced technology with long range Clear imaging against strong back light due to 120 dB true WDR technology Efficient H.265+ compression technology Support on-board storage up to 512 GB (SD card slot) Built-in microphone for real-time audio security 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67)
DS-2CD1743G2-LIZSU (Dahili mikrofon)	 	4MP Smart Hybrit Light Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR High quality imaging with 4 MP resolution Support Human and Vehicle Detection Smart Hybrid Light: advanced technology with long range Clear imaging against strong back light due to 120 dB true WDR technology Support on-board storage up to 512 GB (SD card slot) Efficient H.265+ compression technology Built-in microphone for real-time audio security 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67), vandal proof (IK08)








ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-2CD1643G2-LIZSU/SL (İki Yönlü Ses)	 	4MP Smart Hybrid Light Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR High quality imaging with 4 MP resolution Support Human and Vehicle Detection Smart Hybrid Light: advanced technology with long range Clear imaging even with strong back lighting due to 120 dB WDR technology Efficient H.265+ compression technology Support on-board storage up to 512 GB (SD card slot) Provide real-time security via built-in two-way audio 2.8 to 12 mm motorized varifokal lens for easy installation and monitoring / Water and dust resistant (IP67)
DS-2CD2743G2-IZS	 	4MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
DS-2CD2643G2-IZS	 	4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 60m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
DS-2CD2646G2-IZS (Powered by Darkfighter)	 	4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS((C) model); H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.003 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520,1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm I/O *non-(C) model:1/2.7" Progressive Scan CMOS
DS-2CD2746G2-IZS (Powered by Darkfighter)	 	4MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/3" Progressive Scan CMOS((C) model); H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.003 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520,1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm I/O *non-(C) model:1/2.7" Progressive Scan CMOS
YENİ DS-2XS2T41G1-ID/4G		4MP Solar Kamera High quality imaging with 4 MP resolution Digital WDR /Standalone with solar panel and built-in battery Support human and vehicle detection Provide real-time security via built-in two-way audio Water and dust resistant (IP67) Support 4G (LTE-TDD/LTE-FDD/TD-SCDMA) communication Image Sensor 1/3" Progressive Scan CMOS Solar panel: tilt: -45° to 45°, rotate:-30° to 30° / Fixed focal lens, 4 and 6 mm optional /SIM Card Type : Micro SIM/Uplink And Downlink Data:Cat 4, uplink: 50 Mbps, downlink: 150 Mbps













ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
6MP IP KAMERA		
YENİ DS-2CD1063G2-LIUF	 	6MP Mini IR Bullet Kamera Smart Hybrid Light & MD2.0 High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional);
YENİ DS-2CD1363G2-LIUF	 	6MP Mini IR Dome Kamera Smart Hybrid Light & MD2.0 High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional);
DS-2CD2163G2-IU		6MP Mini IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3200x1800), 25fps/30fps (2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 340m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone
DS-2CD2T63G2-2I	 	6MP IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3200x1800), 25fps/30fps (2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance
YENİ DS-2CD2663G2-IZS	 	6MP IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3200x1800), 25fps/30fps (2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 60m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO
YENİ DS-2CD2763G2-IZS	 	6MP IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3200x1800), 25fps/30fps (2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO
DS-2CD2666G2-IZS		6MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/2.4" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.003 lux@(F1.6, AGC ON), 0 lux with IR; 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 60m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in Audio/Alarm I/O









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
8MP IP KAMERA		
DS-2CD2083G2-IU		8MP IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-U: built-in microphone
DS-2CD2183G2-IU		8MP IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone
DS-2CD2T83G2-2I		8MP IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance
DS-2CD2T86G2-2I (Powered by Darkfighter)		8MP IR Bullet Kamera (H.265+) 120dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.014 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3072×1728, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2I/4I model: up to 50m(2Leds)/80m(4Leds) IR distance
DS-2CD2683G2-IZS		8MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 60m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO
DS-2CD2783G2-IZS		8MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200×1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO













ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2CD2686G2-IZS (Powered by Darkfighter)		8MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) 120dB WDR 1/2" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.011 Lux @ (F1.4, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3072×1728, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 50m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Built-in Audio/Alarm I/O, HIK-Connect cloud service
DS-2CD2786G2-IZS (Powered by Darkfighter)		8MP Motorize Varifokal Lensli IR Dome Kamera (H.265+) 120dB WDR 1/1.8" Progressive Scan CMOS; 265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.011 Lux @ (F1.4, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3072×1728, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Built-in Audio/Alarm I/O, HIK-Connect cloud service
Balıkgözü KAMERA		
YENİ DS-2CD2955FWD-I		5MP Balıkgözü KAMERA 1/2.9" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.016 lux@(F2.2, AGC ON), 0 lux with IR; 20fps(2944×1656), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); F2.2, field of view: 180°(H)x180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 10m(optional); DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
YENİ DS-2CD2935FWD-I		3MP Balıkgözü KAMERA 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.016 lux @(F2.2, AGC ON), 0 lux with IR; 25fps/30fps(2048×1536, 1920×1080); F2.2, field of view: 180°(H)x180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; up to 10m IR(optional); DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
HeatPro Termal KAMERA		
HeatPro		
DS-2TD2617-6/QA		160 × 120 resolution Thermal, 4MP resolution optical Dome Kamera 160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C, F# = 1.1) High accuracy temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F) Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR Support smoking detection algorithm Support sun-reflection filter High quality detector with 10 years guarantee
DS-2TD2617-3/QA		160 × 120 resolution Thermal, 4MP resolution optical Bullet Kamera 160 × 120 resolution, 17 μm, VOx UFPA, NETD < 40 mK (25 °C, F# = 1.1) High accuracy temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8 °C (±14.4 °F) Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR Support smoking detection algorithm Support sun-reflection filter High quality detector with 10 years guarantee



ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2TD2628-3/QA		256 × 192 resolution Thermal, 4MP resolution optical Bullet Kamera 256 × 192 resolution, 12 µm, VOx UFPA, NETD < 40 mK (25°C, F1.0) Video content analysis: vehicle/human classification Temperature exception alarm for fire prevention, -20°C to 150°C (-4°F to 302°F), ± 8°C (± 14.4°F) Support smoking detection algorithm Support sun-reflection filter algorithm Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR ● High quality detector with 10 years guarantee
PTZ KAMERALAR		
IP PTZ KAMERA		
YENİ DS-2DE1C200IW-D3/W		2 MP Network IR Wi-Fi Mini PT Dome (H.265+, 15m IR) High quality imaging with 2 MP resolution; Digital WDR, HLC, BLC, 3D DNR; Good night-time performance with up to 15 m IR; Two-way audio with built-in microphone and speaker; Supports microSD/microSDHC/microSDXC card, up to 256 GB
YENİ DS-2DE2C400MW-DE		4 MP Network IR 2-inch PT Dome (H.265+, 30m IR) High quality imaging with 4 MP resolution; Clear imaging against strong back light due to DWDR technology; 3D DNR technology delivers clean and sharp images; Hik-Connect cloud service and APP for remote management and views of devices; Built-in microphone for real-time audio security; Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB; Water and dust resistant IP66
DS-2DE4215IW-DE (Ayak dahil)	 AcuSense	2MP Network Dış Ortam IR PTZ Kamera (H.265+, 15X, 100m IR, deep learning) 1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 15× optical zoom and 16× digital zoom provide close up views over expansive areas. WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression
DS-2DE4225IW-DE (Ayak dahil)	 AcuSense	2MP Network Dış Ortam IR PTZ Kamera (H.265+, 25X, 100m IR, deep learning) 1/2.8" progressive scan CMOS. High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 25× optical zoom and 16× digital zoom provide close up views over expansive area. WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression
DS-2DE4425IW-DE (Ayak dahil)	 AcuSense	4MP Network Dış Ortam IR PTZ Kamera (H.265+, 25X, 100mt IR) 1/2.8" progressive scan CMOS. High quality imaging with 4 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 25× optical zoom and 16× digital zoom provide close up views over expansive areas WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2DE7A232IW-AEB		4MP Network Dış Ortam IR PTZ Kamera (32X, 200m IR, IP66, deep learning) 1/2.8" progressive scan CMOS. High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. Audio visual alarm: The white flashing light and audible warning can be triggered by certain events 32× optical zoom and 16× digital zoom provide close up views over expansive areas. Expansive night view with up to 200 m IR distance Focuses on human and vehicle targets classification based on deep learning. Face capture: Up to 5 faces captured at the same time
DS-2DE7A432IW-AEB		4MP Network Dış Ortam IR PTZ Kamera (32X, 200m IR, IP66, deep learning) 1/2.8" progressive scan CMOS. High quality imaging with 4 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. Audio visual alarm: The white flashing light and audible warning can be triggered by certain events 32× optical zoom and 16× digital zoom provide close up views over expansive areas. Expansive night view with up to 200 m IR distance Focuses on human and vehicle targets classification based on deep learning. Face capture: Up to 5 faces captured at the same time
YENİ DS-2SE7C432MW-AEB		4MP Network Dış Ortam IR PTZ Kamera (32X, 200m IR, IP66, deep learning) Captures a large area and great details at the same time High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Secures an expansive area with 32× optical zoom and 16× digital zoom Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus Expansive night view with up to 200 m IR distance Supports 24 VAC & Hi-PoE Active strobe light and audio alarm to warn intruders off
ANALOG PTZ KAMERA		
DS-2AE4225TI-D		4-inch 2 MP 25X Powered by DarkFighter Analog Speed Dome 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR, Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:25x, Digital Zoom:16X, Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s, Up the Coax,100mIR,DC12V
NETWORK VIDEO KAYIT CİHAZLARI		
4 KANAL NVR		
DS-7104NI-Q1		4 Kanal NVR (1 SATA, H.265+) 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Plastic)
DS-7104NI-Q1/4P		4 Kanal NVR (1 SATA, H.265+, POE) 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Plastic)
DS-7104NI-Q1/M		4 Kanal NVR (1 SATA, H.265+) 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Metal)




ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-7104NI-Q1/4P/M		4 Kanal NVR (1 SATA, H.265+, POE) 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Metal)
YENİ DS-7604NXI-K1		4 Kanal NVR (1 SATA, H.265+) Up to 1-ch@12 MP or 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity Up to 40 Mbps incoming bandwidth
YENİ DS-7604NXI-K1/4P		4 Kanal NVR (1 SATA, H.265+, POE) Up to 1-ch@12 MP or 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity Up to 40 Mbps incoming bandwidth
8 KANAL NVR		
DS-7108NI-Q1		8 Kanal NVR (1 SATA, H.265+) 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)
DS-7108NI-Q1/M		8 Kanal NVR (1 SATA, H.265+) 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Metal)
DS-7108NI-Q1/8P/M		8 Kanal NVR (1 SATA, H.265+, POE) 60Mbps Bit Rate Input Max (up to 8-ch IP video) 1 SATA interface, 8 independent PoE network interfaces, mini 1U case(Metal)
DS-7608NI-K2/8P		8 Kanal NVR (2 SATA, H.265+, POE) 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1
DS-7608NI-M2		8 Kanal NVR (2 SATA, H.265+) 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, alarm I/O: 4/1, 380 1U case
DS-7608NI-M2/8P		8 Kanal NVR (2 SATA, H.265+ , POE) 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case
16 KANAL NVR		
DS-7616NI-Q2		16 Kanal NVR (2 SATA, H.265+) 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case
DS-7616NI-Q2/16P		16 Kanal NVR (2 SATA, H.265+) 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case
DS-7616NXI-K1		16 Kanal NVR (1 SATA, H.265+) Up to 1-ch@12 MP or 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs










ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-7616NXI-K2/16P		16 Kanal NVR (2 SATA, H.265+, POE) Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs
DS-7716NI-Q4/16P		16 Kanal NVR (4 SATA, H.265+) Up to 4K high-definition live view, storage and playback; Up to 8-ch @ 1080p decoding capacity; Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected; 1 HDMI and 1 VGA interfaces: both interfaces support independent video output; Plug & Play with 16 Power-over-Ethernet (PoE) interfaces
DS-7716NI-K4/16P		16 Kanal NVR (4 SATA, H.265+, POE) Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@12 MP or 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity Plug & play with 16 power-over-Ethernet (PoE) interfaces Up to 160 incoming bandwidth
32 KANAL NVR		
YENİ DS-7632NXI-K2	 AcuSense	32 Kanal NVR (4 SATA, H.265+) Up to 32-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 32-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs
YENİ DS-7732NXI-K4	 AcuSense	32 Kanal NVR (4 SATA, H.265+) Up to 32-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth Adopt Hikvision Acusense technology to minimize manual effort and security costs
YENİ DS-8632NXI-I8/S	 AcuSense	32 Kanal NVR (8 SATA, H.265+) H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on deep learning algorithm Up to 4-ch perimeter protection Up to 4-ch facial recognition for video stream Up to 8-ch facial recognition for face picture Up to 32-ch IP camera inputs Up to 32-ch 1080p decoding capability
64 KANAL NVR		
YENİ DS-7764NI-M4		64 Kanal NVR (4 SATA, H.265+) H.265+/H.265/H.264+/H.264 video formats Up to 64-ch IP camera inputs Up to 2-ch@32 MP + 2-ch@8 MP/10-ch@8 MP/20-ch@4 MP/40-ch@1080p decoding capacity Up to 400 Mbps incoming bandwidth 2 HDMI and 1 VGA interfaces, 8K or dual 4K video outputs
YENİ DS-8664NXI-I8/S	 AcuSense	64 Kanal NVR (8 SATA, H.265+) H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on deep learning algorithm Up to 4-ch perimeter protection Up to 4-ch facial recognition for video stream Up to 8-ch facial recognition for face picture Up to 64-ch IP camera inputs Up to 32-ch 1080p decoding capability









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
HD-TVI ÜRÜNLER (HD-TVI PRODUCTS)		
2MP HD TVI KAMERA 4X1		
DS-2CE16D0T-EXIPF		Harici 1080p Mini IR Bullet Kamera 2MP CMOS Sensor, 1 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output
DS-2CE76D0T-EXIPF		Dahili 1080p Mini IR Dome Kamera 2MP CMOS Sensor, 1 pcs EXIR LEDs, 20m IR, Indoor EXIR Turret, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output
DS-2CE16D0T-EXIF		Harici 1080p Mini IR Bullet Kamera 2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output
YENİ DS-2CE16D0T-EXLPF	 	Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for 4 switchable signals (TVI/AHD/CVI/CVBS)
YENİ DS-2CE76D0T-EXLPF	 	Dahili 1080p Mini IR Dome Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for 4 switchable signals (TVI/AHD/CVI/CVBS)
YENİ DS-2CE16D0T-LPFS (Dahili mikrofon)	 	Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens Up to 25 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) High quality audio with audio over coaxial cable, built-in mic Water and dust resistant (IP67) Smart-Hybrid light, optimize your security with flexible lighting options
YENİ DS-2CE76D0T-LPFS (Dahili mikrofon)	 	1080p Mini IR Dome Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Smart-Hybrid light, optimize your security with flexible lighting options
DS-2CE16D0T-ITPFS		Harici 1080p Mini IR Bullet Kamera Enhancing safety with discreet and economical built-in microphone; Transmits audio over the coaxial cable; EXIR 2.0: advanced infrared technology with 25 m IR distance; Water and dust resistant (IP67); 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2CE17D0T-IT3F		Harici 1080p IR Bullet Kamer 2MP CMOS Sensor, EXIR 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP67, 2.8/3.6/6/8/12mm Lens, Support TVI/AHD/CVI/CVBS video signal output Up to 40 m IR distance for bright night imaging
DS-2CE17D0T-IT5F		Harici 1080p IR Bullet Kamer 2MP CMOS Sensor, EXIR 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP67, 3.6/6/8/12mm Lens, Support TVI/AHD/CVI/CVBS video signal output Up to 80 m IR distance for bright night imaging
YENİ DS-2CE19D0T-VFIT3F		Dahili/Harici 1080p IR Vari-focal Bullet Kamera 2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu, IP67, 2.7-13.5mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output
YENİ DS-2CE5AD0T-VPIT3F		Dahili/Harici 1080p Vari-focal IR Dome Kamera 2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu, IP67, 2.7-13.5mm Vari Focal Lens, IK10, Support HD-TVI/AHD/CVI/CVBS video output
DS-2CE10DF0T-PF	 ColorVu	Harici 1080p IR Bullet Kamera (ColorVu) 2M CMOS Sensor, Outdoor Bullet, 0.001Lux/F1.0, 0 Lux with white Light, 20m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens, 24H Color, Support TVI/AHD/CVI/CVBS video signal output
DS-2CE70DF0T-PF	 ColorVu	Dahili/Harici 1080p IR Dome Kamera (ColorVu) 2M CMOS Sensor, Indoor Turret, 0.001Lux/F1.0, 0 Lux with white Light, 20m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), 2.8/3.6mm Lens, 24H Color, Support TVI/AHD/CVI/CVBS video signal output
YENİ DS-2CE10DF0T-LPFS	 ColorVu Smart Hybrid Light	Harici 1080p IR Bullet Kamera (ColorVu & Smart Hybrid Light) High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)
YENİ DS-2CE70DF0T-LPFS	 ColorVu Smart Hybrid Light	Dahili/Harici 1080p IR Dome Kamera (ColorVu & Smart Hybrid Light) High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-2CE16D0T-LPTS (İki Yönlü Ses)		Dahili/Harici 1080p IR Dome Kamera (Smart Hybrid Light) 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N),EXIR, 30m IR+20m White Light, Outdoor Smart-hybrid-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,Smart Lighting (With Acusense DVR) ,OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens,Built-in mic and speaker,Intelligent noise reduction,Up to 5 meters of two-way audio with echo cancellation. (Need to use XT DVR to support two way audio).
YENİ DS-2CE78D0T-LTS (İki Yönlü Ses)		Dahili/Harici 1080p IR Dome Kamera (Smart Hybrid Light) 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N),EXIR, 30m IR+20m White Light, Outdoor Smart-hybrid-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,Smart Lighting (With Acusense DVR) ,OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens,Built-in mic and speaker,Intelligent noise reduction,Up to 5 meters of two-way audio with echo cancellation. (Need to use XT DVR to support two way audio).
YENİ DS-2CE17D0T-IT1F		Büyük Metal Kasa Uzun IR Kamera (Up to 30 m IR) High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)
YENİ DS-2CE17D0T-IT3F		Büyük Metal Kasa Uzun IR Kamera (Up to 40 m IR) High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)
YENİ DS-2CE17D0T-IT5F		Büyük Metal Kasa Uzun IR Kamera (Up to 80 m IR) High quality imaging with 2 MP, 1920 × 1080 resolution 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 80 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)
5MP HD TVI KAMERA		
DS-2CE76H0T-ITPF		Dahili/Harici 5MP EXIR Dome Kamera (20mt, Plastik) 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Indoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.4/2.8/3.6/6mm Lens,Support TVI/AHD/CVI/CVBS video signal output
DS-2CE16H0T-ITPF		Dahili/Harici 5MP EXIR Bullet Kamera (20mt, Plastik) 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens. Support TVI/AHD/CVI/CVBS video signal output
DS-2CE17H0T-IT3F		Dahili/Harici 5MP EXIR Bullet Kamera (40mt, Metal+Plastik) 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6/8/12mm Lens. Support TVI/AHD/CVI/CVBS video signal output Up to 40 m IR distance for bright night imaging

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-2CE17H0T-IT5F		Dahili/Harici 5MP EXIR Bullet Kamera (80mt, Metal+Plastik) 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 3.6/6/8/12mm Lens, Support TVI/AHD/CVI/CVBS video signal output Up to 80 m IR distance for bright night imaging
DS-2CE16K0T-LPFS (Dahili mikrofon) (Smart ColorVu)	 	Dahili/Harici 3k Hybrid Light Bullet Kamera (20mt, Metal) 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 25m IR+20m White Light, Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output
DS-2CE76K0T-LPFS (Dahili mikrofon)	 	Dahili/Harici 3k Hybrid Light Dome Kamera (20mt, Plastik) 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), EXIR, 20m IR+20m White Light, indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI), Smart Lighting (With Acusense DVR), OSD Menu(Up the Coax), 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output
YENİ DS-2CE10KF0T-LPFS (Dahili mikrofon)	  	Dahili/Harici 3k Hybrid Light Bullet Kamera 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), Outdoor smart hybrid light mini Bullet, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output
YENİ DS-2CE10KF0T-LPFS (Dahili mikrofon)	  	Dahili/Harici 3k Hybrid Light Dome Kamera 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps(Default), Indoor smart hybrid light Turret, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output
HD-TVI KAYIT CİHAZLARI (HD-TVI DVR)		
4 KANAL TURBO HD DVR		
DS-7104HGHI-K1		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, mini 1U case
DS-7104HQHI-K1 (Turbo HD 4.0)		4 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 2-ch IP video input(up to 6-ch IP), 1 SATA interface, CH01: 3MP@15fps, CH01-04:1920×1080P/4MP Lite@15fps/ch, mini 1U case





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-7204HGHI-K1		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, 260 1U case
iDS-7204HQHI-M1/S	 AcuSense	4 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 1-ch face detection or 2-ch false alarm filter, 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01: 3MP @ 15fps, CH01-04:1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output, standalone 1U case
YENİ iDS-7204HQHI-M1/XT	 AcuSense	4 Kanal HD-TVI Kayıt Cihazı (4MP Lite) TVI İki Yönlü Sesi Destekleyen DVR Support TVI Two-way Audio, 1-ch facial recognition or 2-ch advanced model perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, Live view: 3K Lite@20fps/ch, up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case
iDS-7204HUHI-M1/S	 AcuSense	4 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP) 1-ch face detection or 4-ch false alarm filter, 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, support CVBS output, standalone 1U case
8 KANAL TURBO HD DVR		
DS-7108HGHI-K1		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25(P)/30(N) fps/ch, mini 1U case
iDS-7108HQHI-M1/S (Turbo HD 4.0)		8 Kanal HD-TVI Kayıt Cihazı (4MP Lite) full-channel motion detection 2.0 or 4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 4-ch IP video input(up to 12-ch IP), 1 SATA interface CH01-08:1920×1080P @15 fps, 4MP Lite@15fps/ch, mini 1U case
DS-7208HGHI-K1		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25)/(P30(N) fps/ch, 260 1U case
iDS-7208HQHI-M1/S	 AcuSense	8 Kanal HD-TVI Hibrit Kayıt Cihazı (4MP Lite) 1-ch face detection or 4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01 & 02: 3MP @ 15fps, CH01-08:1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output, standalone 1U case
YENİ iDS-7208HQHI-M1/XT	 AcuSense	8 Kanal HD-TVI Kayıt Cihazı (4MP Lite) TVI İki Yönlü Sesi Destekleyen DVR Support TVI Two-way Audio, 2-ch facial recognition or 4-ch advanced model perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, Live view: 3K Lite@20fps/ch, up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
iDS-7208HUHI-M1/S		8 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP) 8-ch Motion Detection 2.0 or 4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, 1 SATA interface, H.265/H.265+ compression, 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, support CVBS output, standalone 1U case
16 KANAL TURBO HD DVR		
DS-7116HGHI-M1		16 Kanal HD-TVI Kayıt Cihazı (1080P) full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, mini 1U case
DS-7116HQHI-K1 (Turbo HD 4.0)		16 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, 8-ch IP video input(up to 24-ch IP),1 SATA interface,CH01-04: 3MP @ 15fps, CH01-16:1920×1080P/4MP Lite@15 fps/ch, 4K UHD output, mini 1U case
DS-7216HGHI-M1		16 Kanal HD-TVI Kayıt Cihazı (1080P Lite) full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, 260 1U case
iDS-7216HQHI-M1/S		16 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 1-ch face detection or 4-ch false alarm filter, 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01-04: 3MP @ 15fps, CH01-16:1920×1080P @15 fps, 4MP Lite@15fps/ch, 4K UHD output, support CVBS output, standalone 1U case
iDS-7216HQHI-M2/S		16 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 1-ch face detection or 4-ch false alarm filter, 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 2 SATA interfaces, CH01-04: 3MP @ 15fps, CH01-16:1920×1080P @15 fps, 4MP Lite@15fps/ch, 4K UHD output, support CVBS output, 380 1U case
YENİ iDS-7216HQHI-M1/XT		16 Kanal HD-TVI Kayıt Cihazı (4MP Lite) TVI İki Yönlü Sesi Destekleyin Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, standalone 1U case
YENİ iDS-7216HQHI-M2/XT		16 Kanal HD-TVI Kayıt Cihazı (4MP Lite) TVI İki Yönlü Sesi Destekleyin DVR Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 1-ch face recognition or 4-ch perimeter protection , 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 2 SATA interfaces, Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, 380 1U case






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ IDS-7216HUHI-M2/S	 AcuSense	16 Kanal HD-TVI Kayıt Cihazı (8MP Lite) 16-ch Motion Detection 2.0 or 4-ch false alarm filter, 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 2 SATA interfaces, H.265/H.265+ compression, 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, support CVBS output, 380 1U case
32 KANAL TURBO HD DVR		
DS-7232HGHI-M2		32 Kanal HD-TVI Kayıt Cihazı (1080P Lite) Deep learning based human and vehicle targets classification of Motion Detection 2.0; H.265 Pro+/H.265 Pro/H.265 video compression; HDTV/AHD/CVI/CVBS/IP video input; Audio via coaxial cable; Up to 18-ch IP camera inputs (up to 5 MP); Up to 1080p Lite@15 fps encoding capability; Max. 1200 m for 720p HDTV signal
YENİ IDS-7232HQHI-M2/S	 AcuSense	32 Kanal HD-TVI Kayıt Cihazı (4MP Lite) 4-ch false alarm filter,32-channel motion 2.0, 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input(up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces,1920×1080P @15 fps, 4MP Lite@15fps/ch, 4K UHD output, support CVBS output, 380 1U case
YENİ IDS-7232HQHI-M2/XT	 AcuSense	32 Kanal HD-TVI Kayıt Cihazı (4MP Lite) TVI İki Yönlü Sesi Destekleyen DVR Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input(up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, 380 1U case
Monitör		
DS-D5019QE	 FULL HD	18.5-inch FHD Monitor •LED backlit technology with full HD 1366 x 768 •19" LED backlight monitor •Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction •Multiple interfaces: HDMI, VGA •Wide viewing angle: Horizontal 90°, Vertical 65° •24/7 operation
DS-D5022FN	 FULL HD	21.5 inch FHD Borderless Monitor •LED backlit technology with full HD 1920×1080 •Wide view angle: 178°(H)/178°(V) •User-friendly operation menu •High reliable components for 7×24 working •1 channel HDMI 1.3 input interface •Three image modes to adapt different environment •Support software spread-spectrum technology to reduce EMI radiation •VESA stand bracket






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-D5024FN	 	23.8 inch FHD Borderless Monitor <ul style="list-style-type: none"> •LED backlit technology with full HD 1920×1080 •Wide view angle: 178°(H)/178°(V) •User-friendly operation menu •High reliable components for 7×24 working •1 channel HDMI 1.3 input interface •Three image modes to adapt different environment •Support software spread-spectrum technology to reduce EMI radiation •VESA stand bracket
DS-D5027FN	 	27 inch FHD Borderless Monitor <ul style="list-style-type: none"> •LED backlit technology with full HD 1920×1080 •Wide view angle: 178°(H)/178°(V) •User-friendly operation menu •High reliable components for 7×24 working •1 channel HDMI 1.3 input interface •Three image modes to adapt different environment •Support software spread-spectrum technology to reduce EMI radiation •VESA stand bracket
DS-D5032QE	 	31.5-inch FHD Monitor <ul style="list-style-type: none"> •LED backlit technology with full HD 1920 x 1080 •32" LED backlight monitor •16.7 million colors display images perfectly •Multiple interfaces: HDMI, VGA, audio in •Built-in speaker •Wide viewing angle: Horizontal 178°, Vertical 178° •24/7 operation •LED backlit technology with full HD 1920×1080 •16.7 million color, display picture perfectly •HDMI support up to 1080P •Multiple inputs: HDMI, VGA •Build-in speaker, Audio 5W*2 •Auto signal input Detection •Smart engine for Phase/Image position/Color calibration •Plastic casing
DS-D5043QE	 	42.5-inch FHD Monitor <ul style="list-style-type: none"> LED backlit technology with full HD 1920 x 1080 43" LED backlight monitor 16.7 million colors display images perfectly Multiple interfaces: HDMI, VGA, audio in Built-in speaker Wide viewing angle: Horizontal 178°, Vertical 178° 24/7 operation LED backlit technology with full HD 1920×1080 16.7 million color, display picture perfectly HDMI support up to 1080P Multiple inputs: HDMI, VGA Build-in speaker, Audio 5W*2 Auto signal input Detection Smart engine for Phase/Image position/Color calibration Plastic casing







NETWORK SWITCH









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-3E0105P-E/M		<p>4 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 4 10/100M RJ45 PoE ports, Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>
YENİ DS-3E0106P-E/M		<p>4 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 4 10/100M RJ45 PoE ports, 4 x 10/100Mbps PoE port, and 2 x 10/100Mbps RJ45 port. IEEE 802.3at/af standard for PoE ports (Max. 35 W PoE output). IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.</p>
DS-3E0109P-E/M		<p>8 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 8 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>
YENİ DS-3E0310P-E/M		<p>8 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 8 10/100M RJ45 PoE ports 8 x 10/100 Mbps PoE port, and 2 x Gigabit RJ45 port. IEEE 802.3at/af standard for PoE ports (Max. 60 W PoE output). IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standard. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. Wire-speed forwarding. Store-and-forward switching. Solid high-strength metal shell. Reliable fan-free design.</p>






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-3E0318P-E/M</p>		<p>16 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 16 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>
<p>YENİ</p> <p>DS-3E0326P-E/M</p>		<p>24 Port Fast Ethernet Unmanaged POE Switch L2, Unmanaged, 24 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>
<p>YENİ</p> <p>DS-3E0505P-E/M</p>		<p>4 Port Gigabit Unmanaged POE Switch L2, Unmanaged, 4 Gigabit POE ports 4 × Gigabit PoE port, 1 × Gigabit RJ45 port IEEE 802.3at/af standard IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard 6 KV surge protection for PoE ports PoE power management Gigabit network access Wire-speed forwarding and non-blocking design Store-and-forward switching Solid high-strength metal shell Reliable fan-free design</p>
<p>YENİ</p> <p>DS-3E0510P-E/M</p>		<p>8 Port Gigabit Unmanaged POE Switch L2, Unmanaged, 8 Gigabit POE ports 8 × Gigabit PoE port, 1 × Gigabit RJ45 port, 1 × Gigabit SFP fiber optical port IEEE 802.3at/af standard IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard 6 KV surge protection for PoE ports PoE power management Gigabit network access Wire-speed forwarding and non-blocking design Store-and-forward switching Solid high-strength metal shell Reliable fan-free design</p>




ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-3E0518P-E/M</p>		<p>16 Port Gigabit Unmanaged POE Switch L2, Unmanaged, 16 Gigabit POE ports 16 × Gigabit PoE port, 2 × Gigabit SFP fiber optical port IEEE 802.3at/af standard IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard 6 KV surge protection for PoE ports PoE power management Gigabit network access Wire-speed forwarding Store-and-forward switching Solid high-strength metal shell</p>
<p>YENİ</p> <p>DS-3E0526P-E/M</p>		<p>24 Port Gigabit Unmanaged POE Switch L2, Unmanaged, 24 Gigabit POE ports 24 × Gigabit PoE port, 2 × Gigabit SFP fiber optical port. IEEE 802.3at/af standard. IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard 6 KV surge protection for PoE ports PoE power management Gigabit network access Wire-speed forwarding Store-and-forward switching Solid high-strength metal shell</p>
<p>DS-3E1105P-EI/M</p>		<p>4 Port Fast Ethernet POE Switch Smart Managed L2, Smart Managed, 4 10/100M RJ45 PoE ports 4 × 10/100 Mbps PoE port, 1 × 10/100 Mbps RJ45 port Total PoE Power Budget 45W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6 KV Surge Protection</p>
<p>YENİ</p> <p>DS-3E1106P-EI/M</p>		<p>4 Port Fast Ethernet Smart POE Switch Cloud management 4 × 10/100 Mbps PoE port, 2 × 10/100 Mbps RJ45 port Total PoE Power Budget 45W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>
<p>DS-3E1309P-EI/M</p>		<p>8 Port Fast Ethernet POE Switch Smart Managed L2, Smart Managed, 8 10/100M RJ45 PoE ports 8 × 100 Mbps PoE RJ45 ports, 1 × Gigabit network RJ45 port. IEEE 802.3at/af standard for PoE ports. Network topology management, alarm push, network health monitor. 6 KV surge protection for PoE ports. Up to 300 m long-range transmission. AF/AT camera can reach up to 300 m in extend mode.</p>





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-3E1310P-EI/M</p>		<p>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</p> <p>L2, Smart Managed, 8 10/100M RJ45 PoE ports Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>
<p>YENİ</p> <p>DS-3E1318P-EI/M</p>		<p>16 Port Fast Ethernet POE Switch Smart Managed Cloud management</p> <p>L2, Smart Managed, 16 10/100M RJ45 PoE ports 16 × 10/100 Mbps PoE port, 1 × Gigabit combo, 1 × Gigabit RJ45 port. IEEE 802.3at/af standard for PoE ports. Network topology management, alarm push, network health monitor. 6 KV surge protection for PoE ports. AF/AT camera can reach up to 300 m in extend mode.</p>
<p>YENİ</p> <p>DS-3E1326P-EI/M</p>		<p>24 Port Fast Ethernet POE Switch Smart Managed Cloud management</p> <p>L2, Smart Managed, 24 10/100M RJ45 PoE ports 24 × 100 Mbps PoE RJ45 ports, 2 × gigabit combos. IEEE 802.3at/af standard for PoE ports. Network topology management, alarm push, network health monitor. 6 KV surge protection for PoE ports. AF/AT camera can reach up to 300 m in extend mode.</p>
<p>YENİ</p> <p>DS-3E1506P-EI/M</p>		<p>4 Port Gigabit Smart POE Switch Smart Managed</p> <p>L2, Smart Managed, 4 Gigabit RJ45 PoE ports 4 × Gigabit PoE port, 2 × Gigabit RJ45 port Total PoE Power Budget 60W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>
<p>YENİ</p> <p>DS-3E1510P-EI/M</p>		<p>8 Port Gigabit Smart POE Switch Smart Managed</p> <p>L2, Smart Managed, 16 Gigabit RJ45 PoE ports 8 × Gigabit PoE port, 2 × Gigabit RJ45 port Total PoE Power Budget 60W Support 802.1Q VLAN Support PoE watchdog to detect and restart the cameras that do not respond Support STP/RSTP Loop prevention Support cable detection to locate failure Up to 300 m Long Range PoE Transmission 6KV Surge Protection</p>





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-3E1518P-EI/M		<p>16 Port Gigabit Smart POE Switch Smart Managed L2, Smart Managed, 16 Gigabit RJ45 PoE ports 16 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 130 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission 6 kV surge protection</p>
DS-3E1526P-EI/M		<p>24 Port Gigabit Smart POE Switch Smart Managed L2, Smart Managed, 24 Gigabit RJ45 PoE ports 24 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 230 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission 6 kV surge protection</p>
DS-3E1518P-EI		<p>16 Port Fast Ethernet POE Switch Smart Managed L2, Smart Managed, 16 Gigabit RJ45 PoE ports 16 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 130 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission 6 kV surge protection</p>
DS-3E1526P-EI		<p>24 Port Fast Ethernet POE Switch Smart Managed L2, Smart Managed, 24 Gigabit RJ45 PoE ports 24 x gigabit PoE RJ45 ports, 1 x gigabit RJ45 port, 1 x gigabit fiber optical port Total PoE power budget 230 W Unified cloud management for security systems Network topology at your fingertips Remote troubleshooting Visualized topology management Up to 300 m long-range PoE transmission 6 kV surge protection</p>
DS-3E0505D-O		<p>5 Port Fast Ethernet Unmanaged Desktop Switch L2, Unmanaged, 5 Gigabit RJ45 ports, desktop plastic switch 5 x 10/100/1000 Mbps ethernet port Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting Plug & play, easy to use.</p>
DS-3E0508D-O		<p>8 Port Fast Ethernet Unmanaged Desktop Switch L2, Unmanaged, 8 Gigabit RJ45 ports, desktop plastic switch 8 x 10/100/1000 Mbps ethernet ports Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting Plug & play, easy to use.</p>






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
DS-3E0105D-O		5 Port Fast Ethernet Unmanaged Desktop Switch L2, Unmanaged, 5 10/100M RJ45 ports, desktop plastic switch 5 x 10/100 Mbps ethernet port Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting installation Plug & play, easy to use
DS-3E0108D-O		8 Port Fast Ethernet Unmanaged Desktop Switch L2, Unmanaged, 8 10/100M RJ45 ports, desktop plastic switch 5 x 10/100 Mbps ethernet port Supports ADI/ADIX Store-and-forward switching Supports MAC address auto-learning and aging Simple, compact body design Supports desktop and wall-mounting installation Plug & play, easy to use
YENİ DS-3WF0EC-5ACT		Elevator Wireless Bridge 5Ghz 867Mbps 500m Elevator Up to 500 m wireless transmission distance 867 Mbps 802.11ac wireless bridge Built-in 8 dBi 2 x 2 MIMO antenna Visualized topology management Real-Time alarm push technology
YENİ DS-3WF0FA-2N/O		Outdoor Wireless Bridge 2.4Ghz 300Mbps 1KM 70° Wireless AP Bridge Up to 1 km wireless transmission distance 300 Mbps 802.11n wireless bridge Built-in 7dBi 2 x 2 MIMO antenna Visualized topology management Real-Time alarm push technology
YENİ DS-3WF02C-5AC/O		Outdoor Wireless Bridge 5Ghz 867Mbps 5km Outdoor Wireless CPE All gigabit LAN ports TDMA supported Quick match through DIP switch Visualized topology management Up to 5 km wireless transmission distance
YENİ DS-3WF03C-5AC/O		Outdoor Wireless Bridge 5Ghz 867Mbps 15km Outdoor Wireless CPE All gigabit LAN ports TDMA supported Quick match through DIP switch Visualized topology management Up to 15 km wireless transmission distance
YENİ DS-3WAP521-SI		Wi-Fi 5 1200M In-Wall Access Point 2 Gigabit LAN Ports with 1 PoE Input 802.11ac Wave 2 1167 Mbps 86 mm Wall Junction Box for Easy Installation 50+ Concurrent User Connections Auto RF Optimization Support Intelligent Fast Roaming
YENİ DS-3WAP522-SI		Wi-Fi 5 1200M Ceiling Access Point 1 Gigabit Port with PoE Input 802.11ac Wave 2 1167 Mbps 80+ Concurrent User Connections Auto RF Optimization Support Intelligent Fast Roaming






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-3WAP622G-SI		Wi-Fi 6 1800M Ceiling Access Point 1 Gigabit Port with PoE Input 802.11ax Wi-Fi 6 1775 Mbps 100+ Concurrent User Connections Auto RF Optimization Support Intelligent Fast Roaming
YENİ DS-3WG210GP-SI		All in One 10 Port PoE AC Router 2 Gigabit WAN Ports with 1 WAN/LAN Switchable 8 Gigabit PoE LAN Ports with 2 LAN/WAN Switchable 75 W PoE Power Budget 1000 Mbps Throughput Recommend 200 Users Access Support Multiple VPNs Including IPsec VPN, L2TP Support Powerful Security Features Including Firewall Policies, DDoS Defending, IP/MAC/URL Filtering, ARP Defending, etc. Support Behavior Management Compact Size for Flexible Deployment
Kablo (Network Cable)		
YENİ DS-1LN6UZC0		Network Kabloları CAT 6 305 m CAT6 UTP Network Cable Stable electrical performance, compliant with ANSI/TIA-568.2-D, IEC61156, ISO/IEC11801. Compliant with RoHS 2.0. • Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the • project. • Excellent performance in the Fluke 90-meter permanent link test while working continuously at 50°C high • temperature. • Excellent performance in the Fluke 100-meter channel test while being continuously loaded with 57V/1A DC power • (PoE). • Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance.
DS-1LN6U-G		Network Kabloları CAT 6 305 m CAT6 UTP Network Cable (Solid Copper, 0.55 mm, Gray) Full diameter 305 m CAT6 network cable Core diameter: 0.55mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance.
DS-1LN6U-G		Network Kabloları CAT 6 305 m CAT6 UTP Network Cable Solid-Bare Copper, Content 99.95%, Full diameter 305 m CAT6 network cable Core diameter: 0.565mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance. Before Aging Tensile Strength (Mpa) ≥13.5, Elongation(%) ≥150, Aging Period (°C×hrs) 100°C×24h×10d, After Aging Tensile Strength(Mpa) ≥12.5, Elongation(%) ≥125, Cold bend(-20±2°C×4h) 8×Cable O.D., No visible cracks, 1.0-250.0MHz Impedance ((Ω) 100±15, 1.0-250.0MHz Delay Skew (ns/100m) ≤45, DC Resistance (Ω/100m) max 9.38, DC Conductor Resistance Unbalance (%) max 5.0,

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
Seslendirme Sistemleri		
DS-QAZ1307G1-E		<p>Network Horn Speaker 7W Insert In</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p> <p>Support two-way audio by SIP</p>
DS-QAZ1307G1T-E		<p>Network Horn Speaker 7W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p> <p>Support two-way audio by SIP</p>
DS-QAZ1325G1T		<p>Network Horn Speaker 25W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p> <p>Support two-way audio by SIP</p>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-QAZ1203G1-BE</p>		<p>Network Ceiling Speaker 3W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support fixed resistance output and can be connected to an external sub speaker to increase the coverage area of the sound field, saving installation and wiring costs.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAZ1206G1-BE</p>		<p>Network Ceiling Speaker 6W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support fixed resistance output and can be connected to an external sub speaker to increase the coverage area of the sound field, saving installation and wiring costs.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAZ0203G1-S</p>		<p>Ceiling Secondary Speaker 3W</p> <p>Connecting the main speaker for sound amplification.</p>
<p>YENİ</p> <p>DS-QAZ0206G1-S</p>		<p>Ceiling Secondary Speaker 6W</p> <p>Connecting the main speaker for sound amplification.</p>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-QAZ1110G1-B</p>		<p>Network Cabinet Speaker 10W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support fixed resistance output and can be connected to an external sub speaker to increase the coverage area of the sound field, saving installation and wiring costs.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAZ1120G1-B</p>		<p>Network Cabinet Speaker 20W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support fixed resistance output and can be connected to an external sub speaker to increase the coverage area of the sound field, saving installation and wiring costs.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAZ0110G1-S</p>		<p>Cabinet Secondary Speaker 10W</p> <p>Connect to the primary speaker to help boost the volume of sound.</p>
<p>YENİ</p> <p>DS-QAZ1430G1</p>		<p>Network Column Speaker 30W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
<p>YENİ</p> <p>DS-QAZ1460G1</p>		<p>Network Column Speaker 60W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAZ14A2G1</p>		<p>Network Column Speaker 120W</p> <p>Adopt high-speed industrial grade dual core chips, built-in NOR Flash+EMMC dual storage, support dual backup of the system to ensure stable and reliable system performance.</p> <p>Support secure startup, user login locking mechanism, and password complexity prompts, support security audit log traceability, and improve system network security.</p> <p>Support batch unified management of remote platforms through IP networks (local area networks/public networks) and flexible configuration of local WEB single machines, while also support local audio collection and playback, adapting to various scene applications.</p> <p>Support alarm input, arming schedule, and audio linkage, support TTS speech synthesis and text broadcasting, with natural and smooth standard male and female dual audio options.</p>
<p>YENİ</p> <p>DS-QAE0203G1-V</p>		<p>Analog Ceiling Speaker 3W</p> <p>Adopting a composite paper fiber sound basin, the sound quality is clear and bright</p> <p>With the design of powerful steel spring clamp, the installation is fast and safe</p> <p>Support ceiling mounting installation with a simple appearance</p>
<p>YENİ</p> <p>DS-QAE0206G1-V</p>		<p>Analog Ceiling Speaker 6W</p> <p>Adopting a composite paper fiber sound basin, the sound quality is clear and bright</p> <p>With the design of powerful steel spring clamp, the installation is fast and safe</p> <p>Support ceiling mounting installation with a simple appearance</p>
<p>YENİ</p> <p>DS-QAE0420G1-V</p>		<p>Analog Column Speaker 20W</p> <p>The speaker unit adopts aerospace magnetic, imported adhesive coating, and lightweight sound film design, with high sensitivity, bright sound, and long transmission distance</p> <p>Adopt professional engineering reinforced plastics with high strength</p> <p>By using L-brackets, the installation surface angle can be adjusted for convenient installation</p> <p>Professional integrated design, supporting IP66 waterproof, with a simple and beautiful appearance</p>

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)
YENİ DS-QAE0A60G1-VB		Analog Amplifier 60W Support four types of audio input: Bluetooth, USB flash drive, microphone, and RCA, with flexible and convenient operation Built-in Bluetooth module, support fast Bluetooth playback Support plugging in the USB flash drive to play audio sources Support independent microphone volume control and two-channel partition volume control Support two-channel audio mixing output Adopt high-strength engineering plastics, sturdy and durable Integrated functional design, convenient and reliable
Kontrol Klavyesi (Key board)		
DS-1600KI		Network Kontrol Klavyesi 10"1" capacitive touchscreen, detachable design of touchscreen and joystick, preview, PTZ and TV wall control, 4-axis joystick
DS-1100KI		Network Kontrol Klavyesi 7" resistive touchscreen, preview, PTZ and TV wall control, 4-axis joystick
DS-1200KI		Network Kontrol Klavyesi 128x64 LED dot matrix screen, PTZ and TV wall control, 4-axis joystick.
DS-1005KI		USB Kontrol Klavyesi USB port, used to control DVR, NVR and software, 4-axis joystick